

Fuel Bed Media Installation Instructions

Volcanic Rocks

FIRE BY **escea.**

Applies to: DF Models

NOTE: Please refer to 630381 DF Series Installation Manual for full details regarding primary and secondary glass removal and re-assembly.

The following images displays a step-by-step process for correct placement of the volcanic rock fuel bed for a DF700 model, the DF960 uses the same process.

Number of Bags Needed: DF700 - 3 x Bags (24 Rocks per Bag), DF960 - 4 x Bags (24 Rocks per Bag)

NOTE: Place rocks individually so that excess dust doesnt get transferred into the fireplace and place the rocks number side down.

WARNING! The volcanic rocks must not cover the pilot or pilot guard. Ensure rocks are placed on the burners in one, even layer. No rocks should be on top of another rock. Incorrect placement may result in poor performance.

- Place large sized volcanic rocks evenly on the burners and infill avoiding the burner or tracking ports. Ensure numbered sides are facing downwards.



- Place medium sized volcanic rocks evenly on the burners and infill. Ensure numbered sides are facing downwards.



- Place small sized volcanic rocks on the burner and infill to fill the remaining gaps. Ensure numbered sides are facing downwards.



NOTE: The position of the rocks will be random. Ensure rocks are placed on the burners in one, even layer. No rocks should be on top of another rock.