



**Mantel Clearance**

1:5

Applicable for:  
**DS1150**  
**DS1400**  
**DS1650**

**notes:**

- DO NOT SCALE OFF THESE DRAWINGS
- All dimensions are in mm.
- This detail is to assist in the installation the DS Series Gas Fire.
- Wall board can be **bonded directly to the faces of the appliance** using construction adhesive. Screw fixing of wall board only, in to wall lining fixing bracket above the glass opening.
- **Do not excessively push back wall board when fixing it to the fire chassis** - use large daubs of adhesive to the chassis, apply wall board and flush finish with edge of the fire reveal.
- 50mm clearance to all combustible surfaces for the first 1200mm of the exhaust flue - zero clearance beyond this point.
- Refer to the **D-Series Materials Guide** for information on materials selection around an Escea Fire. This can be downloaded from [www.escea.com](http://www.escea.com)
- **IMPORTANT:** This technical sheet must be read in conjunction with the **Escea DS Series Installation Manual**, the latest version can be found on our website at [www.escea.com](http://www.escea.com)

GENERAL CONSTRUCTION AND FINISHES SHOWN INDICATIVE ONLY

Contact the **ESCEA Architectural Advisory Team** for assistance with the specification of this fire - [aa@escea.com](mailto:aa@escea.com)