KS Series - Frameless Finish in Cabinetry Panels



Prolonged unprotected exposure to heat may be detrimental to the appearance or long term performance of a wall finish. Combustible and heat sensitive wall panels or finishes must not protrude past the trim, to the glass viewing area. Some scenarios will require a custom solution, to provide further protection.

chase framework at		
minimum chase opening height		
selected ³ / ₄ " (19mm) veneer or laminate cabinetry panel adhesive fixed to fireplace		
wall panel fixing		
adhesive fixing to wall panel		
maintain min. ½" (3mm) gap between wall finish and fireplace trim		
KS See-through and Single Sided Models with g" finish trim		
Applicable for:	Cabinetry Finish	scale 1:2

K\$55 Mesh Barrier Single Sided K\$55 Mesh Barrier See-Through K\$55 Glass Barrier Single Sided K\$55 Glass Barrier See-Through K\$75 Glass Barrier Single Sided K\$75 Glass Barrier See-Through

Notes:

- DO NOT SCALE OFF THESE DRAWINGS
- This detail is to assist in the installation of a **frameless finish** to a KS Series Gas Fireplace.
- This detail is suitable for all four sides of the fireplace glass viewing area.
- Cabinetry panel can be directly bonded to the outer metalwork of the fireplace.
- Follow the manufacturer's instructions for specifying and installing wall panels or finishes. Escea takes no responsibility for material selection.
- The Specifier and/or Installer are responsible for compliance with all relevant Building Codes.
- This technical sheet must be read in conjunction with the requisite Escea KS Series Installation Manual, the latest version can be found on our website at **www.escea.com**.

GENERAL CONSTRUCTION AND FINISHES SHOWN INDICATIVE ONLY

Contact the ESCEA Architectural Advisory Team for assistance with the specification of this fire - aa@escea.com